



8-1/4	11	8-1/8 MAX. 6-1/4 MIN.			15			
7	6-11	5-1/2 MAX. 3-7/8 MIN.			10-1/2			
6-1/2	6	4-1/8 MAX. 2-3/8 MIN.			9-3/4			
'X' DIM. MINIMUM EFFECTIVE HEADER	'A' DIM. TRACK RADIUS	'B' DIM. HEADER TO TOP OF TRACK	'C' DIM. OPENING HEIGHT	'D' DIM. VERTICAL TRACK HEIGHT	'E' DIM. VERTICAL LEG OF HORIZONTAL	'F' DIM. OPENING WIDTH	'G' DIM. DOOR WIDTH	'H' DIM. WALL TO WALL

SEE WHITTING DRAWING B-4259 FOR STANDARD SPECIFICATIONS

TOLERANCES UNLESS OTHERWISE SPECIFIED ARE:
DECIMAL ±.010
FRACTION ±1/16
ANGLES ±1/2°
DO NOT SCALE DRAWING

WHITTING
DOOR MANUFACTURING CORP.
GENERAL OFFICE: 113 CEDAR ST. AKRON, NY. 14001
"DEVELOPER OF THE FIRST PRACTICAL ROLL-UP DOOR IN 1953"

SEA-LOK DOORS
METAL-WOOD

DRAWN BY C.S.P. DATE 8/7/89 CHECKED
APPROVED BY DATE TERRITORY

A	REVISED KEEPER	9/15/83	JM
SYM	DESCRIPTION	DATE	DR
REVISIONS			
TITLE			
OPTIONAL STANDARD INSTALLATION 3/4" GENERAL PURPOSE DOOR			
SCALE 1/2" = 1"	DWG. NO. D - 4656	REV.	A
DISK NO. 2250			