



8	4-1/2	5-3/4	10	1/4			
6-1/2	3-1/4	4-3/4	8	1	8-1/4	5-3/4	10
5-1/4	2	3	6	2-1/4	7-1/2	4-3/4	8
	MINIMUM	MAXIMUM					
A	B	C	K	X	B	C	K
MINIMUM EFFECTIVE HEADER	HEADER TO TOP OF TRACK	HORIZONTAL TRACK RADIUS	HANG DOWN	MINIMUM HEADER W/ NO HANG DOWN	HEADER TO TOP OF TRACK	HORIZONTAL TRACK RADIUS	HANG DOWN

STANDARD SPEC.: B-15819

3/31/08	D	CORRECTED CHART, REMOVED NO HANG DOWN FOR 6" RADIUS	GB	
9/15/08	C	CORRECTED BOTTOM PANEL VIEW RADIUS "C" WAS LABELED "X"	MJS	AF
2/5/08	B	UPDATED TOP BRACKET VIEW; AND 6" RADIUS CHART: A, B, K, X, AND B DIMS	MJS	MB
10/8/06	A	HOR. TRACK LENGTH WAS S-H + 18"	MJS	GB

DO NOT SCALE DRAWING

REVISIONS

WHITING SEA-LOK DOORS

DOOR MANUFACTURING CORP.

GENERAL OFFICE: 113 CEDAR ST. AKRON, NY. 14001

"DEVELOPER OF THE FIRST PRACTICAL ROLL-UP DOOR IN 1953"

DRWN BY DCW DATE 4/20/05 CHECKED TERRITORY

APPROVED BY DATE

TITLE: STANDARD INSTALLATION

1-1/16" PREMIUM HINGED TRUSS II DOOR

SCALE: 1/2"=1" DWG. NO. D-15296 REV. D